(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 12 May 2005 (12.05.2005)

**PCT** 

(10) International Publication Number WO 2005/043618 A1

(51) International Patent Classification<sup>7</sup>: H02M 5/00, G01K 3/00

H01L 23/34,

(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FI-00121 Helsinki (FI).

(21) International Application Number:

PCT/FI2004/000642

- (22) International Filing Date: 29 October 2004 (29.10.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

20031580


30 October 2003 (30.10.2003) I

- (71) Applicant (for all designated States except US): ABB OY [FI/FI]; Strömbergintie 1, FI-00380 Helsinki (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): RONKAINEN, Teemu [FI/FI]; Taavintörmä 6 B, FI-02180 Espoo (FI). HYVÄRINEN, Veikko [FI/FI]; Länsipellontie 3, FI-00390 Helsinki (FI). TIITINEN, Pekka [FI/FI]; Altaintie 22 A, FI-01390 Vantaa (FI).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
- PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

  (84) Designated States (unless otherwise indicated, for every
- kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND ARRANGEMENT IN INVERTER



(57) Abstract: A method and arrangement in connection with an inverter that comprises several power semiconductor components and a control apparatus arranged to control them, the control apparatus being arranged to control the power semiconductor components in response to a control quantity to generate an output voltage. The method comprises the steps of determining the change of the temperature or a quantity affecting the temperature of one or more power semiconductor components, and controlling with the control apparatus the power semiconductor components in response to both the control quantity to generate an output voltage and the change rate of the temperature or quantity affecting the temperature of the power semiconductor components to reduce the temperature change and the change rate.

## WO 2005/043618 A1



## Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,

BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

of inventorship (Rule 4.17(iv)) for US only

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.